

Starvo ChargePro 160

160 kW Ultra-Fast DC Charger

ChargePro 160 is Starvo's high-power, outdoor-ready DC fast charger engineered for high-turnover public sites and fleet depots. Featuring a **PDU Modular design** with pluggable modules for quick installation and maintenance, the integrated design ensures stable and reliable charger operation. The unit includes an **HD Advertising Screen** supporting both static and dynamic advertising displays, making it ideal for commercial environments. Designed for **economical operation** by ordinary electricians to reduce maintenance time and cost, the ChargePro 160 offers dual standard charging support with Gun A and Gun B connectors both supporting the European CCS2 standard.

The ChargePro 160 delivers reliable, high-speed charging with comprehensive safety features and smart connectivity. With a wide DC output voltage range of 150–1000 VDC, this charger accommodates modern EV architectures and future vehicle platforms, while OCPP 1.6J protocol ensures seamless integration with the Starvo platform.




160 kW Power

Output power 160 kW, DC output voltage 150–1000 VDC



OCPP 1.6J

Smart charging profiles, autocharge, GSM/4G modem, 10/100 Base-T Ethernet



IP54 Rated

Indoor and outdoor rated, operating temp -20°C to +55°C



10.1" Touch HMI

LCD touch screen, scan/passcode/plug and play charging modes

Technical Excellence

Electrical Specifications

- **AC input voltage:** 380VAC ±15% (three-phase five-wire)
- **Frequency:** 50~60 Hz
- **Power factor:** ≥ 0.98
- **Current THD:** ≤ 5% Above the half
- **Output power:** 160 kW
- **Recommended upstream circuit breaker:** 250 A
- **DC output voltage:** 150–1000 VDC
- **Constant power output voltage:** 300–1000 VDC
- **DC output current of each gun:** 5–250 A
- **Efficiency:** ≥ 95%
- **Precision of steady current:** ± 1%
- **Precision of steady voltage:** ± 0.5%

Interface and Controller

- **Indicator:** LED (Green, Yellow, Red)
- **User Interface:** 10.1" Touch LCD screen
- **Charging mode:** Scan, passcode, plug and play
- **Network connection:** GSM/4G modem, 10/100 Base-T Ethernet
- **Communication:** OCPP 1.6 core and smart charging profiles, autocharge
- **Operating system:** Starvo apps

Safety and Protection

- **Short circuit protection:** Yes
- **Over load protection:** Yes
- **Over temperature protection:** Yes
- **Leakage protection:** Yes
- **Over and under input voltage protection:** Yes
- **Over and under output voltage protection:** Yes
- **Connector standards:** IEC 61851-1:2017, IEC 61851-23:2014, EN 61851-24:2014, EN 61851-21-1:2018

Environment & General Specifications

Environment

Operating temp -20°C to +55°C, Storage -40°C to +85°C, Humidity ≤95% non-condensing, Altitude 2000 m

General

Cooling: Fan cooling, Noise ≤65 dB, Protection IP54 (indoor and outdoor rated)

Physical

Dimensions 1960 × 1040 × 500 mm, Weight 400 kg, Installation: Floor-stand

Warranty & Cable

Charge cable 5 m, Warranty 1 year, Electric energy measurement: 1.0 Accuracy grade

Smart Features & Connectivity

1

HD Advertising Screen

Supports static and dynamic advertising displays for commercial environments

2

PDU Modular Design

Pluggable modules for quick installation and maintenance with integrated design for stable, reliable operation

3

Multi-Mode Charging

Scan, passcode, and plug-and-play charging options for flexible user access

4

Network Ready

OCPP 1.6J, GSM/4G modem, 10/100 Base-T Ethernet connectivity for full remote management

Comprehensive Safety Systems

The ChargePro 160 incorporates multiple layers of protection to ensure safe, reliable operation in all conditions. Built-in emergency stop functionality provides immediate shutdown capability, while comprehensive voltage and thermal protection safeguard against electrical faults in all environments.



Short Circuit & Overload

Short circuit and overload protection for reliable and safe operation under all load conditions



Voltage Protection

Over and under input/output voltage protection systems for comprehensive electrical safeguarding



Thermal & Leakage

Over-temperature and leakage protection for safe indoor and outdoor operation in all weather conditions

Physical Specifications

Dimensions

H × W × D:
1960 × 1040 × 500 mm

Weight

Total:
400 kg

Installation

Type:
Floor-standing cabinet



Power Modules

4 × high-efficiency power modules (40 kW / 1000 V each) with soft-start and low ripple output



Cable Configuration

2 × CCS2 charging cables with 250A capacity, 5 m standard length, top-mounted cable management

Typical Applications

The ChargePro 160 is ideally suited for diverse commercial and public charging scenarios where high power, reliability, and user experience are paramount. Its robust design and flexible configuration make it the perfect choice for operators seeking to maximize uptime and customer satisfaction.

Public Charging Hubs

High-traffic urban locations requiring fast turnaround and maximum availability

Retail & Hospitality

Shopping centers, hotels, and restaurants offering premium charging amenities

Workplace Charging

Corporate campuses and office buildings supporting employee EV adoption

Fleet Depots

Commercial and municipal fleet operations requiring reliable, high-power charging

Mixed-Use Developments

Residential and commercial complexes with diverse charging requirements

Contact & Ordering Information

PT Starvo Global Energy

Email: sales@starvo.co.id

Phone/WhatsApp: +62 815-666-8618

Website: www.starvo.com

Contact our sales team for detailed specifications, pricing, installation requirements, and customization options. We provide comprehensive support from site assessment through installation and ongoing maintenance.